

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx TUR 18,0009

Issue No: 0

Page 1 of 3

Maus peter 2018 - 10-69

Certificate history:

Issue No. 0 (2018-10-09)

Status:

Current

Date of Issue:

2018-10-09

Applicant:

HIMA Paul Hildebrandt GmbH

Albert-Bassermann-Str. 28

68782 Brühl Germany

Equipment:

HIQuad Module F 3325

Optional accessory:

Type of Protection:

[Ex ib]

Marking:

[Ex ib Gb] IIC/IIB

[Ex ib Db] IIIC/IIIB

Approved for issue on behalf of the IECEx

Certification Body:

Dipl.-Ing. Klauspeter Graffi

Position:

Head of Certification Body

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

- 2. This certificate is not transferable and remains the property of the issuing body.
- 3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

TUV Rheinland Industrie Service GmbH Am Grauen Stein 51105 Cologne Germany





IECEx Certificate of Conformity

Certificate No:

IECEx TUR 18,0009

Issue No: 0

Date of Issue:

2018-10-09

Page 2 of 3

Manufacturer:

HIMA Paul Hildebrandt GmbH

Albert-Bassermann-Str. 28 68782 Brühl

Germany

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2011

Explosive atmospheres - Part 0: General requirements

Edition:6.0

iEC 60079-11: 2011

Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

Edition:6.0

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

DE/TUR/ExTR18.0009/00

Quality Assessment Report:

DE/PTB/QAR11.0008/02



IECEx Certificate of Conformity

Certificate No: IECEx TUR 18.0009 Issue No: 0

Date of Issue: 2018-10-09 Page 3 of 3

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The module F3325 can be used to supply Ex measuring transmitters (0/4 to 20 mA). These transmitters can be installed in potentially explosive atmospheres from zone 1 on.

The cable shield for Ex applications has to be put to potential equalization. In non Ex applications the cable shield is connected to PE bar on the subrack.

Ambient temperature: T_a = 0°C ... + 60°C

Supply circuit UB:

Un = 24 V DC (-15%, +20%) (max. 30VDC)

 $U_{\rm m} = 40V$

(terminal X1 z2(L+), d2(L-))

Intrinsically safe values for the control circuits,

type of protection [Ex ib Gb] IIC/IIB

or [Ex ib Db] IIIC/IIIB

single circuit: parallel circuit:

U₀: 23.2 V U₀: 23.2 V

l_o: 75.6 mA l_o: 151.2mA

P_o: 657.7 mW P_o: 1315.4 mW

Trapezoidal (R = 460.6Ω)

Maximum allowed external capacitance or inductance:

		•		
Exia / Exib	single circuit		parallel circuit	
	IIC	IIB/IIIC/IIIB	IIC	IIB/IIIC/IIIB
Lo	6 mH	25 mH	-	7 mH
c	138 nF	1.01 µF	-	1.01 µF

SPECIFIC CONDITIONS OF USE: NO